

24-Feb-05

REPORT OF NAVIGATION CHANNELS

ER 1130-2-306

YAQUINA BAY AND HARBOR YAQUINA RIVER - OREGON

Minimum depths channel
entering from seaward

Authorized Project NAME OF CHART Name of Channel (Mileage)	Date of Survey	Feet Width	Miles Length	Project Depth	Left Outside Quarter Feet	Mid-Channel for half project width Feet	Right Outside Quarter Feet
YAQUINA BAY AND HARBOR Entrance	12-Oct-04	400	1.0	40	36	38	35
		300	0.5	30	27	35	33
HARBOR Entrance To Turning Basin Turning Basin	21-Sep-04	300	1.5	30	25	28	16
		1200	0.3	30	15	20	23
THE MUD FLATS	29-Aug-01	200	2.0	18	13	12	13
YAQUINA RIVER Weiser Point to 1 Johnson Slough	Jul-00						
		150	3.1	10	10	9	9
Fleisher Slough 2 to Nutes Slough	Jul-00						
		150	2.7	10	9	9	9
Amundson Slough 3 to Toledo	Jul-00	150	3.2	10	6	7	3
Toledo to Mi. 14.5 4 Depoe Slough	Mar-85	150	1.0	10	8	6	8
	Jun-00	200	0.4	10	1	5	1

ENG Form 4021-R (Nov 1990)

Reference is Navigation Chart No. 18581.

NOTE All Depths refer to Mean Lower Low Water.